



ECLIPSEX 300 HYBRID is a excellent IP65 Hybrid, it adoped high efficiency optical system, 17times optical zoom range (3° to 52°). It has accurate X/Y position, professional CMY color mixing system multi-gobo wheels create colorful and vivid effects, and bring a visual feast to the audience! Both for indoor and outdoor applications, it is the ideal lighting equipment for theater, concerts, theme parks, amusement venues, etc.

ECLIPSEX 300 HYBRID IP



PRODUCT PARAMETERS

optical system		/ ippediance		zicetinear opees	
Light source	350W LED	Size	359*219*597mm	Voltage	AC100-240,50/60Hz
Luminous flux	9500lm	Weight	22KG	Max.Power	550W
Angle	3°-52° (5m @ 105,000lx)	casting	Magnalium and Die-cast	Power Connection	power in and out
		Color	Black	Signal socker	3pin or 5pin in and out, RJ45 in and out

Appearance

Control System

Ontical system

Pan/Tilt rotation	540°/270°(8-16bit)	Display	On Board Control, Custom Mode. 0-25Hz Strobe
Dimmer	0-100% 24Bit	Control	DMX/RDM//NFC/Bluetooth/W-DMX (optional)
Cooling	Forced Convection	Con Personality	STANDARD/BASIC/EXTEND

Effect synthetic system

-				
Static Gobo	12 gobos	prism	One 8 prism, bidirectional rotating, speed can be adjusted	
Rotating Gobo		Pantomime	One 6-row mirror, bidirectional rotating, speed can be adjusted	
	Bi-directional rotation	Frost	Light atomization + rainbow disc	
Colors	8 color+white			

CMY Certification Work Environment

CE	Ambient Temp	-20°C-45°C
	IP Rated	IP66

STATIC GOBO




Rotation Gobo







ILLUMINANCE AT DISTANCE



DIMENSIONS







Flectrical Specs